



1109: 6" New Construction IC Airtight Sloped Ceiling Recessed Housing

Specification Images:



Dimensions:

Diameter: 6 3/8"
Length: 14 1/8"
Width: 13 1/2"
Height: 7 3/8"

Weight: 2 lbs.

Features:

- Easily converts to LED with optional replacement lamps

Material List:

1 Housing - Steel / Aluminum - Raw Steel

Safety Listing:

Safety Listed for Damp Locations / IC
 Safety Listed for Damp Locations / IC

Instruction Sheets:

English (HC-430)

Collection: Recessed Lighting

Single IC Sloped Recessed Light Housing, Adjustable to fit varied ceilings from 11 to 45 degree slopes. All housings are thermally protected and UL listed for damp location. This item accommodates up to 75w PAR 38 or 65w BR40 reflector lamp. Easy to install features include junction box with integral Romex connector, breakaway flange, integral captive nail, and adjustable socket plate.

75w PAR38 or 65w BR40

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Adjustable Socket Plate: Adjustable socket assembly provides flexibility in lamping options and precise lamp placement with various trims.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

UPC #:785652110900

Finish: Not Applicable ()

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	1109	1	785652110900	15	15	8	1.042	2.7	175	Yes
Master Pack		6	10785652110907	30	26	9	4.063	19.8	175	Yes
NJ Pallet		96		48	40	73	81.111	316.8		No
NV Pallet		96		48	40	73	81.111	316.8		No

Trim



1121-14
6" Sloped Trim
White Trim / Baffle Aluminum Baffle
White Trim / Baffle Plastic Trim
Maximum Wattage:
75w PAR38
13.5w A19
15w PAR30L
18w PAR38
15w BR30



1121-15
RECESSED TRIM
Black Aluminum Baffle
White Plastic Trim
Maximum Wattage:
75w PAR38
13.5w A19
15w PAR30L
18w PAR38
15w BR30



1122-14
RECESSED TRIM
White Trim / Baffle Plastic Baffle
White Trim / Baffle Plastic Trim
Maximum Wattage:
75w PAR38
13.5w A19
15w PAR30L
18w PAR38
15w BR30



1122-19
RECESSED TRIM
Metallic Gold Plastic Baffle
White Plastic Trim
Maximum Wattage:
75w PAR38
13.5w A19
15w PAR30L
18w PAR38
15w BR30



1122-22
RECESSED TRIM
Polished Aluminum Plastic Baffle
White Plastic Trim
Maximum Wattage:
75w PAR38
13.5w A19
15w PAR30L
18w PAR38
15w BR30