



**1128QC: 6" New Construction IC Recessed Housing with "Quick Connects"**



**Dimensions:**

**Diameter:** 6 3/8"  
**Length:** 13 1/2"  
**Width:** 10 3/4"  
**Height:** 7 7/8"

**Weight:** 2.3 lbs.

**Features:**

- Easily converts to LED with optional replacement lamps
- Meets Title 24 energy efficiency standards

**Material List:**

1 Housing - Aluminum -

**Safety Listing:**

Safety Listed for Damp Locations  
 Safety Listed for Damp Locations

**Instruction Sheets:**

Bilingual (English - French) (HC-438FB)

**Collection:** Recessed Lighting

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs. Also features "Quick Connect" wiring for ease of installation.

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs.

QC - includes Quick Connect wire connectors for easy installation

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Joist Tab: Tab to locate on bottom of joist.

Notch for T-Bar Ceilings: No clips required. Secure bar hanger to T-Bars with wires or screws.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Hinged Door: The hinged junction box door allows full access for wiring while remaining attached to the recess housing.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in. 4 out #12 wire, saves installation time.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

**UPC #:** 785652011283

**Finish:** Not Applicable ( )

**Shipping Information:**

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	1128QC	1	785652011283	14.75	10.75	8	0.734	2.55	100	Yes
Master Pack		6	10785652011280	22.25	20	8.75	2.253	18.15	100	Yes
NJ Pallet		192		48	40	75	83.333	580.8		No
NV Pallet		192		48	40	75	83.333	580.8		No

Trim



1120-15  
**6" Open Trim**

White Steel Trim  
 Maximum Wattage:  
 75w PAR30L  
 65w BR30  
 13.5w A19  
 15w PAR30L  
 15w BR30



1125-14  
**6" Aluminum Baffle Trim**

White Trim / Baffle Aluminum Baffle  
 White Trim / Baffle Aluminum Trim  
 Maximum Wattage:  
 50w PAR30S  
 75w PAR30L  
 65w BR30  
 13.5w A19  
 15w PAR30L  
 15w BR30



1126-14  
**6" Steel Baffle Trim**

White Trim / Baffle Steel Baffle  
 Maximum Wattage:  
 50w PAR30S  
 75w PAR30L  
 65w BR30  
 13.5w A19  
 15w PAR30L  
 15w BR30



1126-15  
**RECESSED TRIM**

Black Steel Baffle  
 White Steel Trim  
 Maximum Wattage:  
 50w PAR30S  
 75w PAR30L  
 65w BR30  
 13.5w A19  
 15w PAR30L  
 15w BR30



1133AT-15  
**6" Flat Glass Shower Trim**

White Glass Diffuser  
 White Plastic Trim  
 Maximum Wattage:  
 40w A19  
 8w A19  
 Suitable For Shower Light



1134-68  
**6" Drop Acrylic Shower Tr**

White Plastic Plastic Diffuser  
 White Plastic Trim  
 Maximum Wattage:  
 40w A19  
 8w A19  
 Suitable For Shower Light



1135AT-15  
**RECESSED TRIM**

Smooth White Glass Diffuser  
 White Steel Trim  
 Maximum Wattage:  
 40w A19  
 8w A19



1136-15  
**6" Eyeball Trim**

White  
 White Steel Trim  
 Maximum Wattage:  
 75w PAR30L  
 65w BR30  
 15w PAR30L  
 15w BR30



1136AT-15  
**6" Eyeball Trim**

White  
 White Steel Trim  
 Maximum Wattage:  
 75w PAR30L  
 65w BR30  
 15w PAR30L  
 15w BR30



1151AT-14  
**6" Baffle Trim**

White Trim / Baffle Aluminum Trim  
 Maximum Wattage:  
 50w PAR30S  
 75w PAR30L  
 90w PAR38  
 65w BR30



1151AT-15  
**RECESSED TRIM**

Black Aluminum Baffle  
 White Aluminum Trim  
 Maximum Wattage:  
 50w PAR30S  
 75w PAR30L  
 90w PAR38  
 65w BR30



1154AT-14  
**6" Open Cone Shower Trim**

White Trim / Baffle Aluminum Baffle  
 White Trim / Baffle Aluminum Trim  
 Maximum Wattage:  
 50w PAR30S  
 75w PAR30L  
 90w PAR38  
 Suitable For Shower Light



1155AT-15

**6" Fresnal Glass Shower T**

Clear Glass Lens

White Aluminum Trim

Maximum Wattage:

40w A19

8w A19

Suitable For Shower Light