



# ASSEMBLY INSTRUCTIONS

STYLE# **21521**

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

*Carefully unpack all lamp parts from carton. We suggest a licensed electrician for all fixture installations.*

1. Take the lamp carefully out of the Carton, and place on a flat surface.
2. Be sure power to the installation point is OFF. Follow the steps below for assembly.
3. Fasten the **Cross bar** to the outlet box. Secure the **Nipple** onto the **Canopy** with **Loop #1**.
4. Adjust the length of wire needed for your installation, remove excess. Adjust chain length as needed. Thread **Quick Link#1** into **Loop #1** on the **Canopy**, then **Quick Link #2** into **Loop #2** on the Fixture **Body**. Hand tighten until snug.
5. Pass the supply wires through the **Canopy** and the hole in the middle of the **Cross Bar**.
6. The power supply wire consists of three wires, one black wire, one white wire and one silver ground wire. Connect the wires as shown.
  - A. Connect the House Ground Wire to the Fixture Ground Wire.
  - B. Connect the House White (or Ribbed) Wire to the Fixture Supply Wire (White or Ribbed Side).
  - C. Connect the House Black (or Red) Wire to the Fixture Supply Wire (Black or Smooth Side).
  - D. Wrap each connected wire with Wire Connector and carefully stuff all of the connected wires into the Outlet Box.
7. Install the correct Bulb (**Bulb Not Included**) into the **Socket** until snug.
8. Thread **Stem** onto **Nipple**, place the **Glass Diffuser** into the **Stem**, then secure the **Tassel** onto the **Stem**. Hand tighten until snug.

**Your installation is completed now. Restore electricity.**

