

# DIONE Ceiling Mount

Universal Voltage: **32-664-24**

# oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_


PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel

<b>LIGHT SOURCE</b>	1 x 9.7W LED, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	11.2W at 120V
<b>RATED LIFE</b>	60000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	2700K, 3500K, 4000K
<b>LUMEN OUTPUT</b>	Delivered: 422 lm (LM-79)
<b>INPUT VOLTAGE</b>	120V to 277V AC, 50/60Hz
<b>DRIVER OUTPUT</b>	350mA, 15W max power
<b>DIMMING</b>	0-10V dimming, 100% to 10% dimming range
<b>CONSTRUCTION</b>	Plated Steel and Glass
<b>DIFFUSER</b>	- Frosted Glass
<b>FINISHES</b>	Satin Nickel (-24)
<b>MOUNTING</b>	4" Octagonal J-Box
<b>STANDARDS</b>	UL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



#### DIMENSIONS

**Dia:** 15.00"

**H:** 2.25"

Order example for standard fixture:

**32-664-24** (x- Voltage - xxx-Sequence # - xx-Finish)

**32:** Universal Voltage

Order example for optional color temperatures: **32-664-2724**

**27:** 2700K, **35:** 3500K, **40:** 4000K

