

DIONE Ceiling Mount

Universal Voltage: **32-665-24**

oxygen

FIXTURE TYPE _____

LOCATION _____


PROJECT _____

DATE _____



-24 Satin Nickel

LIGHT SOURCE	1 x 21.1W LED, 3000K, CRI 90
LUMINAIRE POWER	23.5W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 807 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	700mA, 30W max power
DIMMING	0-10V dimming, 100% to 10% dimming range
CONSTRUCTION	Plated Steel and Glass
DIFFUSER	- Frosted Glass
FINISHES	Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box
STANDARDS	UL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS
Dia: 21.00"
H: 2.25"

Order example for standard fixture:

32-665-24 (x- Voltage - xxx-Sequence # - xx-Finish)

32: Universal Voltage

Order example for optional color temperatures: **32-665-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

