




701LF-HDF

Submitted Model No.: \_\_\_\_\_

Specific Features: \_\_\_\_\_



## LAVATORY FAUCETS

- Single Handle
- Slow Self-Closing
- Deck Mount Basin Faucet
- Single Hole Sink Applications


### STANDARD SPECIFICATIONS:

- Single handle, slow self-closing faucet. For single hole deck mount applications.
- Solid brass fabricated body.
- Metering, vandal resistant, slow-close push handle.
- 4 1/4" (108 mm) rigid spout.
- .5 gpm (1.9 L/min) vandal resistant spray outlet. Total flow per actuation must not exceed .25 gal./cycle (1.0 L/cycle)
- All operating parts must be replaceable from above the deck.
- 1/2"-14 NPSM threaded male inlet shank.



### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- Verified compliant with .25% weighted average Pb content regulations.



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.specselect.com](http://www.specselect.com) for finish options and product availability.

DSP-L-701LF-HDF Rev. B



55 E. 111th Street, Indianapolis, Indiana 46280  
 350 South Edgeware Road, St. Thomas, ON N5P 4L1  
 © 2013 Masco Corporation of Indiana