



## Specifications

8810200

Hot Water Tank Leak  
Detection & Shut-Off Valve

### Application

LeakSmart® Hot Water Tank Leak Detection & Shut-Off Valve detects leaks and shuts off your hot water tanks supply line in less than 5 seconds, protecting you from devastating water damage. Plus, it alerts you when detecting water leaks with audible and visible alarms. The valve is installed on the hot water tanks incoming cold supply. Everything is pre-wired to simplify the installation.

### Features



- Full port valves
- Quick connect wiring
- AC power with battery back-up
- Audible Alarm
- Alarm mute
- 3 LED status lights
- Self test feature

### Product Specifications

- Max. operating pressure: 150 PSI
- Max. shut off pressure: 125 PSI
- Max. ambient temperature: 135° F
- Min. water temperature: 33° F
- Max. water temperature: 190° F
- Valve connection type: 3/4" NPT

### Materials

- Control panel: High performance engineered polymer
- Actuator: High performance engineered polymer
- Valve: Lead free brass



\* Dimensions for reference purposes only

Control panel operates with AC power and has battery back-up (batteries not included)

### Approvals



### Customer Service

Email: [customer-service@leaksmart.com](mailto:customer-service@leaksmart.com)  
Phone: 855-532-5768

### Tech Support

Email: [techsupport@leaksmart.com](mailto:techsupport@leaksmart.com)  
Phone: 855-532-5457