ORBIT - LED Pendant

PD-48932, PD-48948





Fixture Type:	
Catalog Number:	
Project:	
location.	

PRODUCT DESCRIPTION

Streaks of light orbit an invisible circumference.

FEATURES

- Two adjustable orbital light bands for various displays options
- Thin powered cables provide an ultra-clean look
- Driver concealed within the canopy
- Can be mounted on a sloped ceiling
- Color Temperature: 3000K
- CRI: 90
- Rated Life: 50,000 hours

SPECIFICATIONS

Construction: Aluminum with acrylic diffuser


Input: 120V


Dimming: 100% - 10% ELV

Light Source: High output LED

Finish: Black (BK), Satin Nickel (SN)

Standards: ETL/cETL, Damp location listed, JA8 2016 Title 24 Compliant





PD-48932

PD-48948

ORDER NUMBER

Model	Size	Watt	LED Lumens	Delivered Lumens	Finish		
PD-48932	32"	54W	4950	2700	-		
	52		4850	2700	BK	Black	
PD-48948	48"	95W	8550	4750	SN	Satin Nickel	

Example: PD-48932-SN

dweLED.com Phone (800) 526.2588 Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

dweLED retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 2019