

## Beyond Collection One-Light LED Round Ceiling/Wall Mount

Wall or ceiling mounted • Damp location listed



### Description:

One-light LED round wall or ceiling mount fixture. The acrylic diffuser comes with Brushed Nickel knobs for a complete look.

### Specifications:

- Brushed Nickel (-09) (Plated)
- Steel Construction
- White acrylic diffuser
- Replaceable LED module.
- Acrylic diffuser with white, bronze and brushed nickel knobs.
- 1,211 lumens 71.2 lumens/watt
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified

### Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1211/71.2 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

## P2308-0930K9

### Images:



### Dimensions:

Diameter: 12"  
 Depth: 2-7/8"  
 Height: 12"  
 H/CTR: 6" (wall mounted)

Glass  
 Width: 12"  
 Depth: 1-1/2"  
 Height: 12"

## P2308-0930K9

### Dimming Notes:

---

P2308 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron	Nova T	NTELV-300
Lutron	Vierti	VTELV-600
Lutron	Maestro	MAELV-600
Lutron	spacer/system	SPSELV-600
Leviton	Renoir II	AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.