

# FITTER

Ceiling ctc mounted • Damp location listed



## P3408-0930K9

### Description:

One-light LED Flush Mount with a white glass diffuser and replaceable LED Module in a Brushed Nickel finish.

### Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- White glass shade
- 120VA replaceable LED Module (part # 93053641)
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified

### Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1211/71.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

### Images:



### Dimensions:

Diameter: 7-1/2"  
Height: 4-11/16"

Glass  
Width: 7-1/2"

## P3408-0930K9

### Dimming Notes:

---

P3408-0930K9 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.