

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED





Description:

Endorse celebrates the traditional form of a gas-powered coach light with illumination from an LED source. A die-cast aluminum, powdered coated frame created and intriguing visual effect with the clear beveled glass. An optional fluted glass column is offered as an accessory (P8779-31). 3000K, 90+ CRI, 623 lumens (source).

Specifications:

- Black (-31) (powder coat paint)
- Die-cast aluminum Construction
- Clear glass beveled panels (top), Clear glass beveled panels (bottom)
- LED Module is replaceable (part # 93054049)
- · Traditional form.
- · Intriguing visual effect.
- 623 lumens 69.2 lumens/watt per module (source)
- · 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	359/46 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 ℃
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements
	for outdoor use only

P6058-3130K9

Images:



Dimensions:

Width: 10-3/4" Depth: 11-3/4" Height: 17-3/4" H/CTR: 4"

Glass Width: 0-3/16" Length: 7-5/8" Height: 4" Glass 2 Width: 0-3/16" Length: 8-3/4" Height: 9-1/8"



One-Light Outdoor



P6058-3130K9

Dimming Notes:

P6058 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.