

| Project: | | |
|---------------|--|--|
| Fixture Type: | | |
| Location: | | |
| Contact: | | |

EAST HAVEN

Wall mounted · Wet location listed





Description:

Medium LED Wall lantern with contemporary styling and clear seeded glass. 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

Specifications:

Antique Bronze (-20) (powdercoat)
Aluminum construction
Clear Seeded glass
Dimmable (See Dimming Notes)
Back plate covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied
ENERGY STAR® qualified

Performance:

| Number of Modules | 1 | |
|---------------------|--------------------------------|--|
| Input Power | 9w | |
| Input Voltage | 120 V | |
| Input Frequency | 60 Hz | |
| Lumens/LPW | 623/69.2 (LM-79) | |
| ССТ | 3000 K | |
| CRI | 90 | |
| Life (hours) | 60,000 (L70/TM-21) | |
| EMI/RFI | FCC Title 47, Part 15, Class B | |
| Min. Start Temp | -30 | |
| Max. Operating Temp | 30 °C | |
| Warranty | 5 year warranty | |
| Labels | cCSAus Wet location listed | |
| | ENERGY STAR® qualified | |

P6078-2030K9

Images:



Dimensions:

Width: 7-1/2" Height: 9-3/4" Depth: 9-1/8"

H/CTR: 4-3/4" (facing up)



EAST HAVEN



P6078-2030K9

Dimming Notes:

P6078-2030K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.