

Gentry LED 3000K 65" Fan Anvil Iron

300265AVI7 (Anvil Iron)

Project Name: _____
 Location: _____
 Type: _____
 Qty: _____
 Comments: _____



Airflow

| | |
|------------|------|
| CFM (High) | 8061 |
| CFM (Low) | 3189 |
| RPM (High) | 122 |
| RPM (Low) | 51 |

Certifications/Qualifications

| | |
|-----------------|--|
| Location Rating | CSA UL Listed Damp |
| | www.kichler.com/warranty |

Dimensions

| | |
|----------------|-----------------|
| Base Backplate | 5.90 DIA |
| Downrod 1 | 1.00 OD X 6.00" |
| Weight | 33.00 LBS |
| Height | 16.00" |
| Width | 65.00" |

Electrical

| | |
|-------------|----------|
| Amps (High) | 0.45 |
| Amps (Low) | 0.09 |
| Motor Size | DC-165NL |
| Motor Type | DC |

Mounting/Installation

| | |
|---|-----------|
| Minimum Distance from Fan to 7 feet Floor | |
| Interior/Exterior | Exterior |
| Lead Wire Length | 78 |
| Mounting Weight | 30.80 LBS |

Photometrics

| | |
|-----------------------|-------|
| Color Rendering Index | 80 |
| Kelvin Temperature | 3000K |

Primary Lamping

| | |
|------------------------|------------|
| Dimmable | Yes |
| Downlight Included | Yes |
| Downlight Option | Integrated |
| Lamp Included | Integrated |
| Light Source | LED |
| # of Bulbs/LED Modules | 1 |
| Watts (High) | 34 |
| Watts (Low) | 5 |

Product/Ordering Information

| | |
|--------|-------------------|
| SKU | 300265AVI7 |
| Finish | Antique/Burnished |
| Style | Lodge / Country |
| UPC | 783927604000 |

Specifications

| | |
|----------------------|-------------------|
| Blade Finish 1 | DSTRD ANTQ GRY |
| Blade Material | WOOD VENEER |
| Blade Pitch | 14 |
| Blades Included | Yes |
| Blade Sweep | 65 |
| Diffuser Description | Etched Cased Opal |
| Material | STEEL |
| Max Stem Tilt | 18 Degrees |
| Number of Blades | 9 |

Wall Control Included Yes

Additional Finishes



Anvil Iron



Anvil Iron



Distressed Black



Weathered Zinc

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®