# Hatteras Bay™ LED 3000K 52" Fan Weathered Zinc

310018WZC (Weathered Zinc)

Project Name:
Location:
Type:
Qty:
Comments:



Airflow		
CFM (High)	6124	
CFM (Low)	2122	
RPM (High)	146	
RPM (Low)	56	

## Certifications/Qualifications

Location Rating	CSA UL Listed Damp
	www.kichler.com/warranty

$\boldsymbol{\nu}$	 en	sio	1113
_	 		

Base Backplate	6.75 DIA
Downrod 1	1.00 OD X 12.00"
Downrod 2 - Measurement A	16.50"
Downrod 2 - Measurement B	12.50"
Downrod 2 - Measurement C	15.25"
Weight	33.00 LBS
Height	22.50"
Width	52.00"

### Electrical

Amps (High)	0.69	
Amps (Low)	0.28	
Motor Size	172MM X 20MM	
Motor Type	AC	

## Mounting/Installation

Interior/Exterior	Interior	
Floor		
Minimum Distance from Fan to 7 feet		

interior/Exterior	interior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	31.50 LBS

## **Photometrics**

Color Rendering Index	90
Kelvin Temperature	3000K

## **Primary Lamping**

Dimmable	Yes
Downlight Included	Yes
Downlight Option	Integrated
Lamp Included	Integrated
Light Source	LED
# of Bulbs/LED Modules	1
Watts (High)	82
Watts (Low)	15

## Product/Ordering Information

SKU	310018WZC
Finish	Antique/Burnished
Style	Traditional
UPC	783927600194

## Specifications

Blade Finish 1	MEDIUM WALNUT
Blade Finish 2	DARK WALNUT
Blade Material	ABS
Blade Pitch	14
Blades Included	Yes

Blade Sweep	52
Diffuser Description	Fresnel Lens Gloss White Inside-Clear Outside
Material	STEEL, PLYWOOD, GLASS
Max Stem Tilt	22 Degrees
Number of Blades	5
Blades Reversible	Yes
Wall Control Included	Yes

### Additional Finishes



Anvil Iron



Anvil Iron



Weathered Zinc

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference

