## Arvada LED 3000K 44" Fan Brushed Stainless Steel

330090BSS (Brushed Stainless Steel)

Project Name:	
Location:	
Type:	
Qty:	
Comments:	



Airflow		
CFM (High)	3445	
CFM (Low)	1506	
RPM (High)	192	
RPM (Low)	89	

Certifications/Qualifications	ations
RPM (Low)	89
RPM (High)	192

www.kichler.com/warranty

Location Rating

Dimensions	
Base Backplate	6.4 DIA
Downrod 1	1.00 OD X 6.00"
Downrod 2 - Measurement A	10.25"
Downrod 2 - Measurement B	8.50"
Downrod 2 - Measurement C	7.75"
Weight	11.00 LBS
Height	10.25"
Width	44.00"

Electrical	
Amps (High)	0.42
Amps (Low)	0.21
Motor Size	153MM X 12MM
Motor Type	AC

Mounting/Installation  Minimum Distance from Ean to 7 feet		
Motor Type	AC	
Motor Size	153MM X 12MM	
Amps (Low)	0.21	

Minimum Distance from Fan to 7 feet Floor		
Interior/Exterior	Interior	
Lead Wire Length	78	
Low Ceiling Adaptable	Yes, Dual Mount Included	
Mounting Weight	10.30 LBS	

Photometrics		
Color Rendering Index	90	
Kelvin Temperature	3000K	

Primary Lamping	
Dimmable	Yes
Downlight Included	Yes
Downlight Option	Integrated
Lamp Included	Integrated
Light Source	LED
# of Bulbs/LED Modules	1
Watts (High)	52
Watts (Low)	12

watts (Hign)	52	
Watts (Low)	13	
Product/Orderin	ng Information	
SKU	330090BSS	
Finish	Stainless Steel	
Style	Contemporary	
UPC	783927851824	

Specifications		
Blade Finish 1	SILVER	
Blade Finish 2	WALNUT	
Blade Material	WOOD	
Blade Pitch	18	
Blades Included	Yes	

Blade Sweep	44
Diffuser Description	Frosted White
Material	STEEL
Max Stem Tilt	18 Degrees
Number of Blades	5
Blades Reversible	Yes
Wall Control Included	Yes

## **Additional Finishes**



Anvil Iron



Brushed Stainless Steel



Satin Black

## Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

## Notes:

All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference

only.

