

**Concealed Trapway Cadet® Touchless Chair Height Elongated Toilet with Seat**

- ❑ **2989.709 Chair Height Elongated Toilet**
  - Combination tank and bowl with seat
  - Simple hand wave touchless flush technology
  - 2-1/2" diameter sensor module can be installed on wall within 3 feet of toilet or on top of toilet tank itself
  - Siphon action jetted bowl with smooth-sided, concealed trapway
  - Ultra-low consumption (1.28 gpf/4.8 Lpf) utilizes 20% less water
  - Meets EPA WaterSense® criteria
  - 12" (305mm) rough installation
  - 3" flush valve with integrated fill valve
  - 2-1/8" trapway bowl with EverClean® surface included
  - Obtains best 1,000g MaP flush score\*\*
  - Includes top mount, slow-close seat and cover with easy lift-off feature for cleaning
  - Powered by 3 AAA sensor and 4 AA control module batteries (included)
  - Convenient, manual polished chrome override flush actuator on side of tank
  - Limited lifetime warranty on chinaware, limited 5 year warranty on all mechanical parts, and limited 1 year warranty on electronic parts and seat



- ❑ **3075.000 Chair Height Elongated Bowl with Seat**
- ❑ **4000.709 Touchless Tank with Sensor**
- ❑ **5024A.65G Slow-Close Seat Packed with Bowl**

**Nominal Dimensions:**

30-3/16" x 15-13/16" x 30-11/16"  
(767 x 401 x 780mm)

Fixture and toilet seat only, wax ring and supply by others

SEE REVERSE FOR ROUGHING-IN DIMENSIONS

**Compliance Certifications -**

**Meets or Exceeds the Following Specifications:**

- ASME A112.19.2/CSA B45.1 for Vitreous China Fixtures
- US EPA WaterSense® Specification for HETs

**To Be Specified:**

- ❑ Color:  White
- ❑ Supply with stop:

\*\* Maximum Performance (MaP) testing performed by IAPMO R&T Lab. MaP Report conducted by Gauley Associates Ltd. and Koeller and Company.



**MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.**

