Caspain™Hand Held Shower

MODELS:

- VS-3014: 2.5 GPM (9.5 L/min) 15w rate
- VS-3014-E175: 1.75 GPM (6.6 L/min) w rate

FEATURES:

- 5 plungers with 45 sprays, 12 massage jets, 3 spray patterns
- Patented Anystream®plungers resist scale build-up
- Spray adjusting faceplate
- No-Slip rubber handle insert
- Plastic body construction
- Hand held shower has 1/2" -14 NSPM male inlet
- Includes coordinating shower bracket with 1/2" -14 NPTF female inlet, 1/2" - 14 NPSM male outlet with check valve
- Includes 5' metal hose with (1) 1/2" -14 NPSM female inlet and (1) 1/2"-14 NPSM female outlet with check valve
- Corrosion resistant Thishes
- Coordinates with Caspian Collection

STOCK FINISHES:



SPECIALTY FINISHES:



STANDARDS:

- ASME A 112.18.1/ CSA B 125.1 certi
- CEC (CA Energy Commission) certiled, 1.75 GPM only
- WaterSense certiled, 2.0 & 1.75 GPM only


WARRANTY:


Visit www.speakman.com for full product warranty information

- Limited Lifetime Warranty (consumer)
- 1 Year Limited Warranty (commercial)









All dimensions are in inches (millimeters) unless otherwise speci to and are subject to change without notice.

Architect/Engineer Approval Space:

SPEAKMAN 400 ANCHOR MILL ROAD NEW CASTLE, DE 19720

P: 800-537-2107 F: 800-977-2747

W: WWW.SPEAKMAN.COM